

|>

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : GALVEX SU 737  
UFI : UYG0-D0FF-600E-6SUQ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Precision cleaning for ultrasonic processes.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : NGL CLEANING TECHNOLOGY SA.  
Address : Chemin de la Vuarpilliere 7.CH-1260.NYON.SUISSE.  
Telephone : 00.41.(0).22.365.46.66. Fax : 00.41.(0).22.361.81.03.  
contact@ngl-group.com  
www.ngl-group.com

#### 1.4. Emergency telephone number : Urgence 145 24h/24h.

Association/Organisation : Centre Suisse Antipoison - Freiestrasse 16 - CH-8032 Zurich-.

### >SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### > In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).  
Skin irritation, Category 2 (Skin Irrit. 2, H315).  
Serious eye damage, Category 1 (Eye Dam. 1, H318).  
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).  
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

#### 2.2. Label elements

##### > In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 287-494-3 BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.

Hazard statements :

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
------	---

Precautionary statements - Response :

P302 + P352	IF ON SKIN: Wash with plenty of water.
-------------	--

**GALVEX SU 737**

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

P362 + P364

Take off contaminated clothing and wash it before reuse.

**> 2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**
**3.2. Mixtures**
**> Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 0064 CAS: 85536-14-7 EC: 287-494-3 REACH: 01-2119490234-40-XXXX  BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412		10 $\leq$ x % < 25
INDEX: 0002 CAS: 68130-47-2 EC: 614-291-2 REACH: exempted  POLYOXYETHYLENE ALKYL ETHER PHOSPHATE	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318		10 $\leq$ x % < 25
INDEX: 603_030_00_8 CAS: 141-43-5 EC: 205-483-3 REACH: 01-2119486455-28  2-AMINOETHANOL	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 3, H412	[1]	2.5 $\leq$ x % < 10
INDEX: 0003 CAS: 71060-57-6 EC: 615-247-5 REACH: 01-2120119406-62-XXXX  ALCOOL C8-10 ETHOXYLÉS	GHS07 Wng Eye Irrit. 2, H319		1 $\leq$ x % < 2.5

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

**>SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**
**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

**GALVEX SU 737****|> In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

**|> In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**|>SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media****Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**|> 5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)
- nitrogen oxide (NO)
- nitrogen dioxide (NO<sub>2</sub>)
- sulphur dioxide (SO<sub>2</sub>)
- phosphine (PH<sub>3</sub>)

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).



**GALVEX SU 737**

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

Minor spill: Soak up with inert absorbent material

Pump the product into a container and clean the floor with water.

**6.4. Reference to other sections**

No data available.

**>SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**> 7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**> Fire prevention :**

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

**> Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

Stock between 5 °C and 40°C in a dry, well ventilated place.

**> Storage**

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
141-43-5	2.5	1	7.6	3	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
141-43-5	3 ppm	6 ppm			

**GALVEX SU 737**

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
141-43-5		0.2 ppm 0.5 mg/m <sup>3</sup>		1(I)

- China (GBZ 2.1, 2007) :

CAS	TWA :	STEL :	Anm :	TWA :	STEL :	Anm :
141-43-5	8 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>				

- France (INRS - ED984 / 2020-1546) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
141-43-5	1	2.5	3	7.6	-	49. 49 Bis

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
141-43-5	1 ppm 2.5 mg/m <sup>3</sup>	3 ppm 7.6 mg/m <sup>3</sup>		Sk	

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

2-AMINOETHANOL (CAS: 141-43-5)

**Final use:**

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:  
 DNEL :

**Workers.**

 Dermal contact.  
 Long term systemic effects.  
 1 mg/kg body weight/day

 Inhalation.  
 Long term systemic effects.  
 3.3 mg of substance/m<sup>3</sup>

 Inhalation.  
 Long term local effects.  
 3.3 mg of substance/m<sup>3</sup>

|&gt;

**Final use:**

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:  
 DNEL :

**Consumers.**

 Ingestion.  
 Long term systemic effects.  
 3.75 mg/kg body weight/day

 Dermal contact.  
 Long term systemic effects.  
 0.24 mg/kg body weight/day

 Inhalation.  
 Long term systemic effects.  
 2 mg of substance/m<sup>3</sup>

 Inhalation.  
 Long term local effects.  
 2 mg of substance/m<sup>3</sup>

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

|&gt;

**Final use:**

 Exposure method:  
 Potential health effects:  
 DNEL :

 Exposure method:  
 Potential health effects:

**Workers.**

 Dermal contact.  
 Long term systemic effects.  
 85 mg/kg body weight/day

 Inhalation.  
 Long term systemic effects.

**GALVEX SU 737**

DNEL : 6 mg of substance/m3

> <b>Final use:</b>	<b>Consumers.</b>
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.425 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	42.5 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	1.3 mg of substance/m3

|> **Predicted no effect concentration (PNEC):**

2-AMINOETHANOL (CAS: 141-43-5)

Environmental compartment:	Soil.
PNEC :	1.29 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.07 mg/l
Environmental compartment:	Sea water.
PNEC :	0.007 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.028 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.357 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.0357 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	100 mg/l

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Environmental compartment:	Soil.
PNEC :	35 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.268 mg/l
Environmental compartment:	Sea water.
PNEC :	0.027 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.017 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	8.1 mg/kg

**GALVEX SU 737**

Environmental compartment: PNEC :	Marine sediment. 6.8 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 3.43 mg/m3

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.  
Store personal protective equipment in a clean place, away from the work area.  
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.  
Use eye protectors designed to protect against liquid splashes  
Before handling, wear safety goggles with protective sides accordance with standard EN166.  
In the event of high danger, protect the face with a face shield.  
Prescription glasses are not considered as protection.  
Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.  
Provide eyewash stations in facilities where the product is handled constantly.

**|> - Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.  
Gloves must be selected according to the application and duration of use at the workstation.  
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.  
Type of gloves recommended :  
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))  
- Butyl Rubber (Isobutylene-isoprene copolymer)

**|> - Body protection**

Avoid skin contact.  
Wear suitable protective clothing.  
Suitable type of protective clothing :  
In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.  
In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.  
Suitable type of protective boots :  
In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.  
In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.  
Work clothing worn by personnel shall be laundered regularly.  
After contact with the product, all parts of the body that have been soiled must be washed.

**>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**Physical state**

Physical state : Viscous liquid.

**Colour**

Color: yellow/orange

**> Odour**

Odour threshold : Not stated.

Odour: characteristic

**> Melting point**

Melting point/melting range : Not specified.

**> Freezing point**

Freezing point / Freezing range : Not stated.

**> Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : Not specified.

**> Flammability**

Flammability (solid, gas) : Not stated.

**> Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

**Flash point**

Flash Point Interval : FP > 100°C.

**Auto-ignition temperature**

Self-ignition temperature : Not specified.

**Decomposition temperature**

Decomposition point/decomposition range : Not specified.

**> pH**

pH : 7.20 .

Neutral.

pH (aqueous solution) : 8.1

**> Kinematic viscosity**

Viscosity : Not stated.

**> Solubility**

Water solubility : Dilutable.

Fat solubility : Not stated.

**> Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Not relevant.

**Density and/or relative density**

Density : 1.039

**> Relative vapour density**

Vapour density : Not stated.

**9.2. Other information**

% VOC : 0

**> 9.2.1. Information with regard to physical hazard classes**

No data available.

**> 9.2.2. Other safety characteristics**

No data available.





**GALVEX SU 737**

**Miscibility**

Miscibility : 100%

**>SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**> 10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**> 10.4. Conditions to avoid**

No data available.

**> 10.5. Incompatible materials**

Keep away from :

- strong acids
- strong bases

**> 10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)
- nitrogen oxide (NO)
- nitrogen dioxide (NO<sub>2</sub>)
- sulphur dioxide (SO<sub>2</sub>)
- phosphine (PH<sub>3</sub>)

**>SECTION 11 : TOXICOLOGICAL INFORMATION**

**> 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Harmful if swallowed.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

**> 11.1.1. Substances**

**> Acute toxicity :**

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Oral route : 300 < LD50 <= 2000 mg/kg  
Species : Rat  
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 402 (Acute Dermal Toxicity)

**> Skin corrosion/skin irritation :**

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**GALVEX SU 737**

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**|> Respiratory or skin sensitisation :**

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Guinea Pig Maximisation Test (GMPT) : Non-sensitiser.  
Species : Guinea pig**|> 11.1.2. Mixture****|> Skin corrosion/skin irritation :**

Corrosivity : No observed effect.

**|>SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity****|> 12.1.1. Substances**

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Fish toxicity : LC50 < 10 mg/l  
Species : Lepomis macrochirus  
Duration of exposure : 96 h  
Other guidelineNOEC = 1 mg/l  
Species : Lepomis macrochirus  
Duration of exposure : 28 daysCrustacean toxicity : EC50 < 10 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)NOEC > 1 mg/l  
Species : Others

Algae toxicity : Species : Others

Aquatic plant toxicity : NOEC > 4 mg/l  
Species : Others  
Duration of exposure : 28 days**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability****|> 12.2.1. Substances**

2-AMINOETHANOL (CAS: 141-43-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. (CAS: 85536-14-7)

Biodegradability : Rapidly degradable.



**GALVEX SU 737**

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**|> German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 2 : Hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

07 06 04 \* other organic solvents, washing liquids and mother liquors

**|>SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**|> 14.1. UN number or ID number**

-

**|> 14.2. UN proper shipping name**

-

**|> 14.3. Transport hazard class(es)**

-

**|> 14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**|>SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**|> - Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

**GALVEX SU 737****- Container information:**

No data available.

**- Particular provisions :**

No data available.

**>> - German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 2 : Hazardous for water.

**15.2. Chemical safety assessment**

No data available.

**>>SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**>> Wording of the phrases mentioned in section 3 :**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**>> Abbreviations :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.



**GALVEX SU 737**

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

|> Modification compared to the previous version