



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Silicone Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 147
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340 Telefax: ++49(0)7041-963429
e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone number: ++49(0)7041-96340
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F+ - Extremely flammable, Xi - Irritant, N - Dangerous for the environment
R phrases:
Extremely flammable.
Irritating to skin.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Vapours may cause drowsiness and dizziness.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

Hydrocarbons, C6, isoalkane, <5% n-hexane

Signal word: Danger
Pictograms: GHS02-GHS07-GHS09



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 2 of 8

Precautionary statements

P102	Keep out of reach of children.
P501	Dispose of contents/container to Dispose of this material and its container to hazardous or special waste collection point..
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.
P210	Keep away from heat. No Smoking.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
265-151-9	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	25-50 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
01-2119484651-34		
203-448-7	butane	25-50 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	10-25 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 3 of 8

Suitable extinguishing mediaCarbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water. Foam. Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

Further information on handling

No data available

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.
- No smoking.**Advice on storage compatibility**

Do not store together with: Material, rich in oxygen, oxidizing.

Further information on storage conditions

No data available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 4 of 8

Additional advice on limit values

No data available

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	-0,5 °C
Flash point:	< 0 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	300 °C
Vapour pressure: (at 20 °C)	2100 hPa
Vapour pressure: (at 50 °C)	4900 hPa
Density:	0,725 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 5 of 8

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
106-97-8	butane	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS

Irritation and corrosivity

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances
Classified as hazardous waste.**Waste disposal number of contaminated packaging**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 6 of 8

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 7 of 8

Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)
E0

Air transport (ICAO)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Special Provisions: A145 A167
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
E0
: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 80 % (520 g/l)

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information**Relevant R-phrases (Number and full text)**

- 11 Highly flammable.
- 12 Extremely flammable.
- 38 Irritating to skin.
- 51 Toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

Relevant H- and EUH-phrases (Number and full text)

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Silicone Spray

Print date: 29.05.2015

Product code: VB_12

Page 8 of 8

H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)