

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product All-purpose cleaner
Code-Nr. 100 741

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor

LAMPERT Werktechnik GmbH
Ettlebener Str. 27, 97440 Werneck
Tel.: 09722 9459 0, Fax: 09722 9459 100
Mail: mail@lampert.info, Web: www.lampert.info

Advice

LAMPERT Werktechnik GmbH
Ettlebener Str. 27, 97440 Werneck
Tel.: 09722 9459 0, Fax: 09722 9459 100
Mail: mail@lampert.info, Web: www.lampert.info

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
64-17-5	200-578-6	ethanol	3 - 9,9	Flam. Liq. 2, H225
106-97-8	203-448-7	butane	3 - 9,9	Flam. Gas 1, H220 / Press. Gas
109-66-0	203-692-4	pentane	10 - 24,9	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
74-98-6	200-827-9	propane	3 - 9,9	Flam. Gas 1, H220 / Press. Gas
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	50 - 74,99	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336

REACH

CAS No	Name	REACH registration number
74-98-6	propane	01-2119486944-21
64742-49-0	Naphtha (petroleum), hydrotreated light	01-2119475514-35

Labelling for contents according to regulation (EC) No 648/2004, annex VII

30 % and more aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

If swallowed seek medical advice immediately and show the doctor packing or label.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam
Dry powder
Carbon dioxide
water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting
In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains or bodies of water.
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Allow to vaporise.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.
Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Protect from heat and sunlight.
Vapours can form an explosive mixture with air.
Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store together with food.

Further information on storage conditions

keep dry and cool. The local authorities' regulations relating to the storage of compressed gas packagings (aerosol cans) must be adhered to.
Protect from heat and direct solar radiation.
Keep container in a well-ventilated place
Storage temperature may not exceed 50°C (=122°F).
Recommended storage temperature: room temperature.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
64-17-5	ethanol	8 hours	1920	1000	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0	pentane	8 hours	3000	1000	

DNEL-/PNEC-values

DNEL worker

CAS No	Substance name	Value	Code	Remark
64-17-5	ethanol	343 mg/kg	DNEL long-term dermal (systemic)	
		950 mg/m3	DNEL acute inhalative (systemic)	
		1900 mg/m3	DNEL acute inhalative (local)	
64742-49-0	Naphtha (petroleum), hydrotreated light	2035 mg/m3	DNEL long-term inhalative (systemic)	
		773 mg/kg bw/day	DNEL long-term dermal (systemic)	

DNEL Consumer

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	608 mg/m ³	DNEL long-term inhalative (systemic)	
		699 mg/kg bw/day	DNEL long-term oral (repeated)	
		699 mg/kg bw/day	DNEL long-term dermal (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification: Nitrile rubber

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

aerosol

Colour

colourless

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				

	Value	Temperature	at	Method	Remark
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	200 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,8 Vol-%				
Upper explosion limit	15 Vol-%				
Vapour pressure	573 hPa	20 °C			
Relative density	0,669 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water	5 g/l	20 °C			
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Solvent content	100 %				
Oxidising properties					
No information available.					
Explosive properties					
The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .					
9.2. Other information					
No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5840 mg/kg	rat		Information concerns to main component.
LD50 acute dermal	> 2920 mg/kg	rabbit		Informations concern to main component.
LC50 acute inhalation	> 25 mg/l (4 h)	rat		Informations concern to main component.
Skin irritation	irritant			
Eye irritation	non-irritant			
Skin sensitization	non-sensitizing			

Experiences made from practice

Irritates respiratory tract.

Irritates mucous membranes.

Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 4,26 mg/l (96 h)	Oncorhynchus mykiss		Pentane
Daphnia	EC50 3 mg/l (48 h)	Daphnia magna		Information refers to the main component.
Algae	NOEC 7,51 mg/l (72 h)	Pseudokirchneriella subcapitata		Pentane

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Toxic to fishes.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

Harmful to fishes and bacteria.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

15 01 10*

Name of waste

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS (Naphtha (petroleum), hydrotreated light)	AEROSOLS (Naphtha (petroleum), hydrotreated light)	Aerosols, flammable (Naphtha (petroleum), hydrotreated light)
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 100 %

VOC value 669 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.