



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

*** SECTION 1: Identification of the substance/mixture and of the company/undertaking**

*** 1.1 Product identifier**

Trade name/designation SUPROL PRO
Unique Formula Identifier UFI: EP50-K0A9-6002-G6N4
Product category PC-CLN-OTH Other cleaning, care and maintenance products (excludes biocidal products)

Hazard components

mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of uses [SU]

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU3 Industrial uses

Use of the substance/mixture

Ready-for-use water-free rinsing solution for the water-free watch-cleaning and ready-for-use water-displacing agent after aqueous cleaning and rinsing.

Uses advised against

Do not use for injecting or spraying.

1.3 Details of the supplier of the safety data sheet

Supplier

Elma Schmidbauer GmbH
Gottlieb-Daimler-Str. 17
D-78224 Singen (Htwl.)
Telephone +49 7731 882-0
Telefax +49 7731 882-266
E-mail info@elma-ultrasonic.com
Website www.elma-ultrasonic.com

Department responsible for information:
Chemie/Labor: Email: chemlab@elma-ultrasonic.com

*** 1.4 Emergency telephone number**

Vergiftungs-Informationen-Zentrale Freiburg (Sprache/Language: DE, +49 761 19240
EN)

*** SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]	Classification procedure
Flam. Liq. 3, H226	On basis of test data.
Eye Irrit. 2, H319	Calculation method.
STOT SE 3, H336	Calculation method.
Asp. Tox. 1, H304	Expert judgement and weight of evidence determination.
Aquatic Chronic 3, H412	Calculation method.

Hazard statements for physical hazards

H226 Flammable liquid and vapour.

Hazard statements for health hazards

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

Hazard statements for environmental hazards

H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS02



GHS07



GHS08

Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P405 Store locked up.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

*** 2.3 Other hazards**

*** Adverse human health effects and symptoms**

Skin Irrit. 3 H316: Causes mild skin irritation.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

*** Adverse environmental effects**

Aquatic Acute 3 H402: Harmful to aquatic life.
This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Results of PBT and vPvB assessment

The product does not contain any PBT-/vPvB-substances according to the recipe.

*** SECTION 3: Composition / information on ingredients**

3.1 Substances

not applicable

*** 3.2 Mixtures**

Hazardous ingredients

CAS No.	EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
	927-241-2	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]	90 - 100 weight-%	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412; EUH066	



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

CAS No.	EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
763-32-6	212-110-8	3-methylbut-3-en-1-ol	< 3 weight-%	Flam. Liq. 3; H226 Eye Dam. 1; H318 STOT RE 2; H373	

REACH No.	Substance name
01-2119471843-32	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]
01-2119438443-41	3-methylbut-3-en-1-ol

Additional information

Mixture of hydrocarbons, aromatics removed, with additives of alkoxy.

*** SECTION 4: First aid measures**

*** 4.1 Description of first aid measures**

*** General information**

Remove contaminated, saturated clothing immediately.
Remove casualty to fresh air and keep warm and at rest.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.
In the event of symptoms refer for medical treatment.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Following ingestion

Do NOT induce vomiting.
Call a physician immediately.
If swallowed seek medical advice immediately and show the doctor packing or label.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Dizziness

Effects

In case of ingestion risk of pulmonary oedema and pneumonia.

*** 4.3 Indication of any immediate medical attention and special treatment needed**

*** Notes for the doctor**

Subsequent observance for pneumonia and lung oedema.
If swallowed, flush stomach adding activated charcoal.
Keep under medical supervision for at least 48 hours.

*** SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam
Extinguishing powder
Carbon dioxide (CO₂)
Water spray jet



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Flammable vapor-air-mixture are more heavy than air. Inflammation over far distance is possible.

In the event of fire the following can be released:

Carbon monoxide

* **5.3 Advice for firefighters**

* **Special protective equipment for firefighters**

Do not inhale explosion and combustion gases.

* **Additional information**

Fire class

B (Fires of liquids or liquid turning substances).

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

* **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

For emergency responders

Ensure adequate ventilation.

Remove persons to safety.

Personal protection equipment

Use personal protection.

Remove all sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For containment

Send in suitable containers for recovery or disposal.

Take up with absorbent material (e.g. oil binder).

* **6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

* **SECTION 7: Handling and storage**



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

*** 7.1 Precautions for safe handling**

*** Protective measures**
Keep away from sources of ignition - No smoking.
Handle and open container with care.
Avoid:
generation/formation of aerosols
Do not inhale gases/vapours/aerosols.
Use only in well-ventilated areas.
Keep container tightly closed.
Avoid contact with eyes and skin.
Keep limited supplies at workplace.
Vapours are heavier than air.
Provide room air exhaust at ground level.
Suitable container/equipment material:
Material, solvent-resistant
Vapours can form explosive mixtures with air.
Ignitable mixtures can be formed in the empty container.
Take precautionary measures against static discharges.
Keep the packing dry and well sealed to prevent contamination and absorption of humidity.
Keep in a cool, well-ventilated place.

Advices on general occupational hygiene

Make available sufficient washing facilities
Keep away from food and drink.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Ensure adequate ventilation of the storage area.
Keep only in unopened original container.

Storage class

3 Flammable liquids

Materials to avoid

Do not store together with:
Oxidising agent

Further information on storage conditions

Keep locked up and out of reach of children.
Keep locked up.
Store in a place accessible by authorized persons only.
Protect from heat and direct solar radiation.
Storage time: 3 years.

7.3 Specific end use(s)

Recommendation

no further

*** SECTION 8: Exposure controls/personal protection**

*** 8.1 Control parameters**

*** DNEL worker**

CAS No.	Substance name	DNEL value	DNEL type	Remark
	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]	77 mg/kg bw/day	long-term dermal (systemic)	Assessment factor 24
	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]	871 mg/m ³	long-term inhalative (systemic)	Assessment factor 6



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

8.2 Exposure controls

Appropriate engineering controls

Technical measures to prevent exposure

Technical exhaustion if there is a long-term exposition

Personal protection equipment

Eye/face protection

tightly fitting goggles

Hand protection

Gloves (solvent-resistant)

Glove material specification [make/type, thickness]: FKM, 0.4mm.

Respiratory protection

Respiratory protection necessary at:

insufficient exhaust

prolonged exposure

Suitable respiratory protection apparatus:

Short term: filter apparatus, filter A

Environmental exposure controls

Technical measures to prevent exposure

Avoid penetration into the subsoil/soil.

Do not discharge into the drains/surface waters/groundwater.

Additional information

Occupational exposure limits for mixtures of hydrocarbons.

*** SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

colourless

Odour

characteristic

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:			not determined
Melting point/freezing point	Solidifying point < -20 °C		
Boiling point or initial boiling point and boiling range	>80- 170 °C		
flammability	solid		not applicable
flammability	gaseous		not applicable
Lower and upper explosion limit	Upper explosion limit 8 Vol-%		
Lower and upper explosion limit	Lower explosion limit 0.6 Vol-%		
Flash point	23- 28 °C		
Auto-ignition temperature	> 200 °C		
Decomposition temperature	> 200 °C		



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

	Value	Method	Source, Remark
pH	in delivery state		not applicable
Viscosity	kinematic 0.8- 1.1 mm ² /s (20°C)		
Solubility(ies)	Water solubility		partially soluble
Partition coefficient n-octanol/water (log value)	approx.4.5- 6.5		Value of hydrocarbon components.
Vapour pressure	27 hPa (20°C)		
Density and/or relative density	0.74- 0.77 g/cm ³ (20°C)		
Relative vapour density	> 1		
particle characteristics			not applicable (liquid).

* **9.2 Other information**

* **Information with regard to physical hazard classes**

* **Explosives**

* **Assessment/classification**

The mixture does not contain any explosive substances (CLP I 2.1.4.3 a).
CLP I 2.1.4.3 a: The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with explosive properties.

* **flammable gases**

* **Assessment/classification**

not applicable (liquid).

* **Aerosols**

* **Assessment/classification**

not relevant - no aerosol.
The classification criteria for this hazard class are not met by definition.

* **Oxidising gas**

* **Assessment/classification**

not applicable (liquid).

* **Gases under pressure**

* **Assessment/classification**

not applicable (liquid - no dissolved gas).

* **flammable liquids**

* **Assessment/classification**

Flam. Liq. 3 H226: Flash point ≥ 23 °C and ≤ 60 °C.
Flammable liquid and vapour.

* **flammable solids**

* **Assessment/classification**

not applicable (liquid).

* **Self-reactive substances and mixtures**

* **Assessment/classification**

The mixture does not contain any self-reactive substances (CLP I 2.8.4.2 a).
CLP I 2.8.4.2 a: There are no chemical groups present in the molecule associated with explosive or self reactive properties.



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

* **Pyrophoric liquids**

* **Assessment/classification**

The mixture does not contain any pyrophoric substances - not spontaneously flammable (CLP I 2.9.4.1).
CLP I 2.9.4.1: The classification procedure for pyrophoric liquids need not be applied when experience in manufacture or handling shows that the substance or mixture does not ignite spontaneously on coming into contact with air at normal temperatures (i.e. the substance is known to be stable at room temperature for prolonged periods of time (days)).

* **Pyrophoric solids**

* **Assessment/classification**

not applicable (liquid).

* **self-heating substances and mixtures**

* **Assessment/classification**

The mixture does not contain any self-heating substances.

* **Substances or mixtures which, in contact with water, emit flammable gases**

* **Assessment/classification**

not relevant - in contact with water releases no flammable gases (CLP I 2.12.4.1).
CLP I 2.12.4.1: The classification procedure for this class need not be applied if: (a) the chemical structure of the substance or mixture does not contain metals or metalloids; or (b) experience in production or handling shows that the substance or mixture does not react with water, e.g. the substance is manufactured with water or washed with water; or (c) the substance or mixture is known to be soluble in water to form a stable mixture.

* **Oxidising liquids**

* **Assessment/classification**

The mixture does not contain any oxidising substances.

* **Oxidising solids**

* **Assessment/classification**

not applicable (liquid).

* **Organic peroxides**

* **Assessment/classification**

The mixture does not contain any organic peroxides.

* **Corrosive to metals**

Safety characteristics

Value	Method, Result	Source, Remark
		The mixture does not contain any substances corrosive to metals.

* **Assessment/classification**

Based on available data, the classification criteria are not met.

* **Desensitised explosives**

* **Assessment/classification**

The mixture does not contain any desensitised explosive substances.

Other safety characteristics

Value	Method	Source, Remark
Evaporation rate		Mixture of dearomatized hydrocarbons: 0.46-0.56 (ASTM D3539) / 20-23 (DIN 53170) .
Solvent content	100 %	
Explosive properties		Not classified as explosive. Vapours can form an explosive mixture with air.



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

	Value	Method	Source, Remark
Oxidising properties			none

* **Other information**
Vapours are heavier than air.

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapours can form an explosive mixture with air.
No further hazardous reactions known if used as directed.

10.2 Chemical stability

Stable at ambient temperature.

10.3 Possibility of hazardous reactions

Reactions with oxidising agents.

10.4 Conditions to avoid

Heat and direct solar radiation.
Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.5 Incompatible materials

Oxidising agent

10.6 Hazardous decomposition products

No decomposition if used as directed.

* **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

* **Acute toxicity**

Animal data

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	> 5000 mg/kg	ATE: Acute Toxicity Estimate	
Acute dermal toxicity	> 5000 mg/kg	ATE: Acute Toxicity Estimate	
Acute inhalation toxicity	Acute inhalation toxicity (vapour) > 50 mg/L	ATE: Acute Toxicity Estimate	

* **Assessment/classification**
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Animal data

Result / Evaluation	Method	Source, Remark
slightly irritant	Calculation method.	

Serious eye damage/irritation



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

Animal data

Result / Evaluation	Method	Source, Remark
Irritant.	Calculation method.	

* **Sensitisation to the respiratory tract**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

Skin sensitisation

Animal data

Result / Evaluation	Dose / Concentration	Method	Source, Remark
not sensitising.		Calculation method.	

* **Germ cell mutagenicity**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

* **Carcinogenicity**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

* **Reproductive toxicity**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

* **Overall Assessment on CMR properties**

The mixture is not classified as mutagen / not classified as carcinogen / not classified as reproductive toxicant.

* **STOT-single exposure**

* **STOT SE 1 and 2**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

* **STOT SE 3**

* **Irritation to respiratory tract**

* **Assessment/classification**
Based on available data, the classification criteria are not met.

* **Narcotic effects**

* **Assessment/classification**
Narcotic effect: STOT SE 3 H336: May cause drowsiness or dizziness.

* **STOT-repeated exposure**

* **Other information**
Contains 3-methylbut-3-en-1-ol.

* **Assessment/classification**
The mixture is not classified as specific target organ toxicant (repeated exposure).
Based on available data, the classification criteria are not met.

* **Aspiration hazard**

* **Experimental data**

	Value	Method	Source, Remark
Cinematic viscosity (40°C):	< 20.5 mm ² /s		
Hydrocarbon content (%):	90- 100		



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

* **Assessment/classification**
Aspiration hazard: Asp. Tox. 1 H304: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Symptoms related to the physical, chemical and toxicological characteristics

	Effective dose	Method,Evaluation	Source, Remark
Endocrine disrupting properties			This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

* **Other information**

benzene: < 10 ppm.
Has degreasing effect on the skin.
The product has not been tested. The information is derived from products of similar composition.

* **SECTION 12: Ecological information**

* **12.1 Toxicity**

Aquatic toxicity

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: >10- 31 mg/L mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] LL50 >10- 30 mg/L Species Oncorhynchus mykiss (Rainbow trout) Test duration 96 h	calculated. OECD 203	
Chronic (long-term) fish toxicity	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] NOELR 0.182 mg/L Test duration 28 d	QSAR	
Acute (short-term) toxicity to crustacea	EC50 23- 47 mg/L mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] EL50 >22- 46 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	calculated. OECD 202	
Chronic (long-term) toxicity to aquatic invertebrate	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] NOELR 0.317 mg/L Test duration 21 d	QSAR	

**SUPROL PRO**

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) toxicity to algae and cyanobacteria	EC50 601 mg/L	calculated.	
	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] EL50 > 1000 mg/L Species Pseudokirchneriella subcapitata Test duration 72 h	OECD 201	
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	NOELR: < 1 mg/L		
	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics] NOELR: < 1 mg/L Species Pseudokirchneriella subcapitata Test duration 72 h	OECD 201	
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		

*** Assessment/classification**

Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

	Value	Method	Source, Remark
Biodegradation			Readily biodegradable (according to OECD criteria).
Biodegradation	Degradation rate 89 % Test duration 28 d	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	mixture of dearomatized hydrocarbons (<0,1% aromatics) [Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics]
Biodegradation	Degradation rate 70- 80 % Test duration 28 d	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	CAS No.763-32-6 3-methylbut-3-en-1-ol

12.3 Bioaccumulative potential**Assessment/classification**

Mixture of dearomatized hydrocarbons: Because of the n-octanol/water partition coefficient (log Pow) accumulation in organisms is possible.

3-methylbut-3-en-1-ol: Significant accumulation in organisms is not expected (log Pow: 0.89).

12.4 Mobility in soil**Assessment/classification**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: The product may evaporate relatively quickly. The proportion of the distribution on the sediment layer and waste water solids is probably < 10%.

3-methylbut-3-en-1-ol: Adsorption on soil is not expected.



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

12.5 Results of PBT and vPvB assessment

The product does not contain any PBT-/vPvB-substances according to the recipe.

12.6 Endocrine disrupting properties

	Effective dose	Method,Evaluation	Source, Remark
Endocrine disrupting properties			This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

	Value	Method	Source, Remark
Ozone depletion potential (ODP):			Based on available data, the classification criteria are not met.

Additional ecotoxicological information

	Value	Method	Source, Remark
Theoretical oxygen demand (ThOD):	3.34 g/g	calculated.	
AOX			The product does not contain any organically bound halogens according to the recipe.

Additional information

Acute aquatic environmental hazards: Aquatic Acute 3 H402: Harmful to aquatic life.
Chronic aquatic environmental hazards: Aquatic Chronic 3 H412: Harmful to aquatic life with long lasting effects.
Do not allow uncontrolled discharge of product into the environment.
Product is not allowed to be discharged into the ground water or aquatic environment.
No further relevant informations available.

*** SECTION 13: Disposal considerations**

*** 13.1 Waste treatment methods**

Waste codes/waste designations according to EWC/AVV

Waste code product	Waste name
140603 *	other solvents and solvent mixtures

Waste code packaging	Waste name
150110 *	packaging containing residues of or contaminated by hazardous substances

Appropriate disposal / Product

Do not dispose with household waste. Do not discharge into the drains.
Dispose of waste according to applicable legislation.

*** Appropriate disposal / Package**

Non-contaminated packages may be recycled.
Handle contaminated packages in the same way as the substance itself.

Remark

Send to a hazardous waste incinerator facility under observation of official regulations.



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1 UN number or ID number	3295	3295	3295
14.2 UN proper shipping name	HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.	Hydrocarbons, liquid, n.o.s.
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No	No	No
14.6 Special precautions for user	none		
14.7 Maritime transport in bulk according to IMO instruments	not relevant		

Land transport (ADR/RID)

UN number or ID number 3295
UN proper shipping name HYDROCARBONS, LIQUID, N.O.S.
Transport hazard class(es) 3
Hazard label(s) 3
Classification code F1
Packing group III
Environmental hazards No
Limited quantity (LQ) 5 L
Special provisions -
Tunnel restriction code D/E

Sea transport (IMDG)

UN number or ID number 3295
UN proper shipping name HYDROCARBONS, LIQUID, N.O.S.
Transport hazard class(es) 3
Packing group III
Environmental hazards No
Limited quantity (LQ) 5 L
Marine pollutant No
EmS F-E, S-D

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number 3295
UN proper shipping name Hydrocarbons, liquid, n.o.s.
Transport hazard class(es) 3
Packing group III
Environmental hazards No



SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

* **SECTION 15: Regulatory information**

* **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

* **EU legislation**

Authorisations
not relevant

* **Restrictions on use**

Regulation (EC) No 1907/2006 (REACH), Annex XVII No 3 + 40 - not relevant if used as directed.
Regulation (EC) No 1907/2006 (REACH), Annex XVII No 75 - not relevant if used as directed.

* **Restrictions of occupation**

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

To follow:
Directive 2012/18/EU, Annex I: P5c.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC

VOC content, ready-to-use condition 100 %
VOC content, delivery state 100 %

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment were not carried out.

* **SECTION 16: Other information**

* **Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM: American Society for Testing and Materials

ATE: Acute Toxicity Estimate

AVV: Waste Shipment Ordinance (DE)

DGR: Dangerous Goods Regulations (IATA)

DIN: German Institute for Standardization / German Industrial Standard

DNEL: derived no-effect level

EL50: Effective Loading 50 %

EmS: emergency procedures

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

JArbSchG: Youth Labor Protection Act (DE)

LL50: Lethal Loading 50 %

NOELR: No Observed Effect Level

OECD: Organisation for Economic Cooperation and Development

PBT: persistent and bioaccumulative and toxic

QSAR: Quantitative Structure-Activity Relationship

RID: Dangerous goods regulations for transport by rail

TI: Technical Instruction

TRGS: Technical Rules for Hazardous Substances

VOC: Volatile organic compounds

vPvB: very persistent, very bioaccumulative

Key literature references and sources for data

Own measurements.

European Chemicals Agency, <http://echa.europa.eu/>.

Informations from our suppliers.

Additional information

National and local regulations concerning chemicals shall be observed.

These data are given according to our actual knowledge about this product. This data sheet does not correspond to an assurance by virtue of a contract for properties of the product.



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SUPROL PRO

Print date 21.11.2022
Revision date 04.10.2022
Version 2.2 (en)
replaces version of 25.10.2017 (2.1)

Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Indication of changes

* Data changed compared with the previous version