

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

L&R Ultraschallreinigungsmittel #566

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

cleaning solution

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Bullnheimer & Co GmbH & CO KG	
Street:	Im Tal 12	
Place:	D-86179 Augsburg	
Telephone:	+49 821 80850-0	Telefax: +49 821 80850-90
e-mail:	info@bullnheimer.de	
Contact person:	Michela Da Re' Okunmeh	Telephone: +49 821 80850-25
e-mail:	dare@bullnheimer.de	
Internet:	http://www.bullnheimer.de	

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Stoddard solvent; Low boiling point naphtha - unspecified

Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha

2-aminoethanol; ethanolamine

propan-1-ol; n-propanol

Signal word: Danger

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 2 of 14

Pictograms:



Hazard statements

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.
 The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
8052-41-3	Stoddard solvent; Low boiling point naphtha - unspecified	60 - 70 %
	232-489-3	649-345-00-4
	Flam. Liq. 3, STOT RE 1, Asp. Tox. 1; H226 H372 H304	
64742-89-8	Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha	15 - 25 %
	265-192-2	649-267-00-0
	Asp. Tox. 1; H304	
112-80-1	Oleic acid	5 - 10 %
	204-007-1	
2807-30-9	2-(propyloxy)ethanol; EGPE	1 - 5 %
	220-548-6	603-095-00-2
	Acute Tox. 4, Eye Irrit. 2; H312 H319	
141-43-5	2-aminoethanol; ethanolamine	1 - 5 %
	205-483-3	603-030-00-8
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B; H332 H312 H302 H314	

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 3 of 14

71-23-8	propan-1-ol; n-propanol			1 - 5 %
	200-746-9	603-003-00-0		
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 4 of 14

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides.

Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 5 of 14

Protect against: UV-radiation/sunlight. heat. Humidity frost.
storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. (DIN EN 374)

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 6 of 14

exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - amber
Odour:	characteristic
pH-Value:	11,2

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	>100 °C
Flash point:	23,9 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	1 vol. %
Upper explosion limits:	8 vol. %
Ignition temperature:	not determined
Decomposition temperature:	not determined

Oxidizing properties

none.

Vapour pressure: (at 37,8 °C)	226,67 hPa
Density:	0,795 g/cm ³
Water solubility:	emulsion

Solubility in other solvents

not determined

Viscosity / dynamic: (at 40 °C)	not determined
Viscosity / kinematic: (at 20 °C)	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 7 of 14

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat. moisture.
 In use may form flammable/explosive vapour-air mixture.
 Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.
 The product has not been tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-89-8	Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rat	ECHA Dossier	
	inhalation (4 h) aerosol	LC50 5,610 mg/l	Rat	ECHA Dossier	
112-80-1	Oleic acid				
	oral	LD50 >5000 mg/kg		RTECS	
2807-30-9	2-(propyloxy)ethanol; EGPE				
	dermal	ATE 1100 mg/kg			
141-43-5	2-aminoethanol; ethanolamine				
	oral	LD50 1515 mg/kg	Rat Ratte	ECHA Dossier	
	dermal	LD50 1025 mg/kg	Rabbit	IUCLID	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 8 of 14

	inhalation vapour	ATE	11 mg/l			
	inhalation aerosol	ATE	1,5 mg/l			
71-23-8	propan-1-ol; n-propanol					
	dermal	LD50	(>2000) mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50	(>33,8) mg/l	Rat	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (2-aminoethanol; ethanolamine)

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Stoddard solvent; Low boiling point naphtha - unspecified)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

Further information

Solvent:

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting. Nausea.

Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-89-8	Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha					
	Acute algae toxicity	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50	4,5 mg/l	48 h	Daphnia magna	REACH Dossier OECD Guideline 202
	Fish toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	REACH Dossier OECD Guideline 211
	Crustacea toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	REACH Dossier OECD Guideline 211
112-80-1	Oleic acid					
	Acute fish toxicity	LC50	205 mg/l	96 h	Pimephales promelas	US EPA

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 9 of 14

141-43-5		2-aminoethanol; ethanolamine					
	Acute fish toxicity	LC50	150 mg/l	96 h	Onchorhynchus mykiss	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	(2,8)	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50	(65) mg/l	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC mg/l	(0,85)	21 d	Daphnia magna	ECHA Dossier	
71-23-8		propan-1-ol; n-propanol					
	Acute fish toxicity	LC50 mg/l	4555	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	9170		Pseudokirchnerella subcapitata (48h)	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Gammarus pulex	ECHA Dossier	
	Crustacea toxicity	NOEC mg/l	>100	21 d	Daphnia magna	ECHA Dossier	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
64742-89-8	Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha				
	ISO/DIS 14593	90	28	ECHA Dossier	
	Biodegradable.				
141-43-5	2-aminoethanol; ethanolamine				
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	>90%	21	ECHA Dossier	
	Readily biodegradable (according to OECD criteria).				
71-23-8	propan-1-ol; n-propanol				
	-	75%	20	ECHA Dossier	
	Biodegradable.				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-80-1	Oleic acid	7,7
141-43-5	2-aminoethanol; ethanolamine	-1,91 (25°C)
71-23-8	propan-1-ol; n-propanol	0,2

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 10 of 14

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

Waste disposal number of waste from residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

Waste disposal number of used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (naphtha; propan-1-ol; n-propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (naphtha; propan-1-ol; n-propanol)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 11 of 14

14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 274 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (naphtha; propan-1-ol; n-propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: NO
 Special Provisions: 223, 274, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (naphtha; propan-1-ol; n-propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

See section 8.

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 12 of 14

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 2-(propyloxy)ethanol; EGPE; 2-aminoethanol; ethanolamine

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Changes

Rev. 1.00; Initial release 14.08.2019

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert

AVV: Abfallverzeichnisverordnung

CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 13 of 14

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

L&R Ultraschallreinigungsmittel #566

Revision date: 14.08.2019

Product code: 5308.566

Page 14 of 14

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)