Telefax: ++49(0)7041-963429



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 1 of 7

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Silicone Spray

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Uses advised against

Reserved for industrial and professional use.

# 1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340

e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone ++49(0)7041-96340

**number:** Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

**SECTION 2: Hazards identification** 

### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

## Regulation (EC) No. 1272/2008

### Hazard components for labelling

Hydrocarbons, C6, isoalkane, <5% n-hexane

Signal word: Danger

Pictograms:







# **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

# **Precautionary statements**

P102 Keep out of reach of children.

P501 Dispose of contents/container to Dispose of this material and its container to hazardous or

special waste collection point..

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 2 of 7

P271 Use only outdoors or in a well-ventilated area.

P251 Do not pierce or burn, even after use. P210 Keep away from heat. No Smoking.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha, <5% n-hexane				
	931-254-9				
	Flam. Liq. 2, STOT SE 3, Asp. Tox.	1, Aquatic Chronic 2; H225 H336 H3			
106-97-8	butane				
	203-448-7	601-004-00-0			
	Flam. Gas 1; H220				
74-98-6	propane				
	200-827-9	601-003-00-5			
	Flam. Gas 1; H220				

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

# After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

### After ingestion

If swallowed, immediately drink: Water.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

### Unsuitable extinguishing media

Water. Foam. Water with tenside additive. Water.

## 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 3 of 7

bursting.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

### 6.3. Methods and material for containment and cleaning up

Ventilate affected area.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

## Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

# Further information on handling

No data available

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

### Further information on storage conditions

No data available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

### Additional advice on limit values

No data available

#### 8.2. Exposure controls



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 4 of 7





### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

## Eye/face protection

Tightly sealed safety glasses.

### **Hand protection**

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Protective clothing:

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

### Changes in the physical state

-0,5 °C
< 0 °C
1,2 vol. % 9,4 vol. %
300 °C
2100 hPa
4900 hPa

Density: 0,725 g/cm<sup>3</sup>

### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No data available

## 10.2. Chemical stability

No data available

# 10.3. Possibility of hazardous reactions

No data available



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 5 of 7

#### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

#### 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

No data available

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
106-97-8	butane				
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS

#### Irritation and corrosivity

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

#### Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 12.3. Bioaccumulative potential

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

#### **Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

# Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

### Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 6 of 7

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

### Other applicable information (land transport)

E<sub>0</sub>

## Inland waterways transport (ADN)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

### Other applicable information (inland waterways transport)

E0

### Marine transport (IMDG)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277
EmS: F-D, S-U

### Other applicable information (marine transport)

E0



according to Regulation (EC) No 1907/2006

# Silicone Spray

Print date: 30.01.2017 Product code: VB\_12 Page 7 of 7

### Air transport (ICAO)

**14.1. UN number:** UN1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Special Provisions: A145 A167 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

### Other applicable information (air transport)

E0 : Y203

## 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

2004/42/EC (VOC): 80 % (520 g/l)

**National regulatory information** 

Water contaminating class (D): 2 - water contaminating

### **SECTION 16: Other information**

# Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)